

```
#-----
# dot.zshrc // sogal
#-----

# Prompt:
PROMPT="%B%F{magenta}%n%b %F{green}%~ %f> "
RPROMPT=" [%B%F{red}%T%f%b]"
#autoload -U promptinit
#promptinit
#prompt walters

# Path:
export
PATH=$PATH/usr/bin:/bin:/sbin:/home/sogal/bin:/usr/sbin:/usr/local/bin:/usr/
games/:

# Word delimiters:
autoload -U select-word-style
select-word-style bash
WORDCHARS='*?_-.[]~=&;!#$%^(){}<>\'

# Sourcer le .bash_aliases :
[ -f ~/.bash_aliases ] && source ~/.bash_aliases

# Colorisation des manpages:
man() {
    env LESS_TERMCAP_mb=$'\E[01;31m' \
    LESS_TERMCAP_md=$'\E[01;38;5;104m' \
    LESS_TERMCAP_me=$'\E[0m' \
    LESS_TERMCAP_se=$'\E[0m' \
    LESS_TERMCAP_so=$'\E[1;31m' \
    LESS_TERMCAP_ue=$'\E[0m' \
    LESS_TERMCAP_us=$'\E[04;33m' \
    man "$@"
}

# Colorisation syntaxique avec less:
export LESSOPEN="| /usr/share/source-highlight/src-hilite-lesspipe.sh %s"
export LESS=' -R '

# Définir le titre du terminal:
if [ "$SHELL" = '/bin/zsh' ]
then
    case $TERM in
    st*|*term)
        precmd() { print -Pn "\e]0;%n@m:%~\a" }
        preexec () { print -Pn "\e]0;%n@m:$1\a" }
        ;;
    esac
fi
```

```
# Pour utiliser polipo et privoxy
http_proxy=http://192.168.1.253:8123/
HTTP_PROXY=$http_proxy
export http_proxy HTTP_PROXY

# Autres options:
setopt hash_list_all           # hash everything before completion
setopt completealiases        # complete alisases
setopt always_to_end          # when completing from the middle of a word,
move the cursor to the end of the word
setopt complete_in_word       # allow completion from within a word/phrase
setopt correct                 # spelling correction for commands
setopt list_ambiguous         # complete as much of a completion until it
gets ambiguous.

zstyle ':completion::complete:*' use-cache on           # completion
caching, use rehash to clear
zstyle ':completion:*' cache-path ~/.zsh/cache          # cache path
zstyle ':completion:*' matcher-list 'm:{a-zA-Z}={A-Za-z}' # ignore case
zstyle ':completion:*' menu select=2                  # menu if nb
items > 2
zstyle ':completion:*' list-colors ${(s.:.)LS_COLORS}  # colorz !
zstyle ':completion:*::::' completer _expand _complete _ignored _approximate
# list of completers to use

# sections completion !
zstyle ':completion:*' verbose yes
zstyle ':completion*:descriptions' format $'\e[00;32m%d'
zstyle ':completion*:messages' format $'\e[00;31m%d'
zstyle ':completion:*' group-name ''
zstyle ':completion*:manuals' separate-sections true

zstyle ':completion*:processes' command 'ps -au$USER'
zstyle ':completion*:*:kill:*' menu yes select
zstyle ':completion*:kill:*' force-list always
zstyle ':completion*:*:kill*:processes' list-colors "=(#b)
#[[0-9]]#)*=29=34"
zstyle ':completion*:*:killall:*' menu yes select
zstyle ':completion*:killall:*' force-list always
zstyle ':completion*:processes-names' command 'ps c -u ${USER} -o command |
uniq'

# Key Bindings:
bindkey -e
bindkey '\e[1;5C' forward-word
bindkey '\e[1;5D' backward-word

# The following lines were added by compinstall
zstyle ':completion:*' completer _expand _complete _ignored _approximate
zstyle ':completion:*' list-colors ''
zstyle ':completion:*' max-errors 1
```

```
zstyle ':completion:*' menu select=2
zstyle ':completion:*' prompt 'err: %e'
zstyle ':completion:*' select-prompt %SScrolling active: current selection
at %p%s
zstyle :compinstall filename '/home/sogal/.zshrc'

autoload -Uz compinit
compinit
# End of lines added by compinstall

# Lines configured by zsh-newuser-install
HISTFILE=~/.zhistfile
HISTSIZE=3000
SAVEHIST=3000
setopt notify
unsetopt beep
# End of lines configured by zsh-newuser-install
```

From:

<http://debian-facile.org/> - **Documentation - Wiki**

Permanent link:

<http://debian-facile.org/utilisateurs:sogal:config:zshrc>



Last update: **23/08/2015 11:29**